



FOSC OPGW

FOSC Optical Grounding Wire Closure

The FOSC OPGW, part of the FOSC 400 closure family, is a single-ended closure system specially developed for use on the optical grounding wires of overhead electrical power lines.

The closure is suitable for use above ground; it can be attached to high voltage towers, poles, walls or other support structures.

Features

- Single-ended design with valve
- A galvanized steel mounting frame holds the thermoplastic dome and base and the OPGW cable clamps
- A pole mounting kit is included which allows the closure to be mounted on a traverse strut of a high voltage tower without the need to drill holes in the metal construction
- A stainless steel shot-gun protection enclosure is optionally available. It permits the termination and sealing of:
 - 2 OPGW cables
 - 2 ADSS or conventional buried fiber optic cables
- Cable seals are manufactured from heatshrinkable material
- Internal storage utilizes FOSC splice trays which are hinged for access to any splice without disturbing other trays
- Butt splice closure
- Heat-shrink technology
- Hinging splice trays
- Superior fiber management for optical grounding wires

Ordering Information

Closure size	FOSC 400 A4	FOSC 400 B4	
Dimensions (in mm)			
Width x depth	202 x 240	202 x 240	
Length without protection enclosure	605	715	
Length with protection enclosure	7300	730	
Splice capacity (in # of fibers)			
	Splices at tray edges	Splices in modules	
Number of splice trays*	3	2	4 (6)*
Single fiber**	72	48	144**
Cable ports			
4 round ports for 1 cable each with ø range			

* The B4 version can be fitted with 5 or 6 trays. However, this option must be selected when the closure is first ordered, as it requires special engineering and the standard base cannot be upgraded to accept 5 or 6 trays.

** Splicing capacity is based on 45 mm fusion splice protectors.

Ordering Information

FOSC - OPGW - XX XXX - X - X X X

Closure size

A4	FOSC 400 A4
B4	FOSC 400 B4

Type of splicing trays

Tray Options		
Closure Size	Splices at Tray edges	Splices at modules
A4	S08, S24, A24	12, 24
B4	S12, S24, A24	12, 24

(S or A for SMOUV or ANT splice protectors)
(S08, S12, S24 European style splice trays)

Pre-installed trays

1, 2 or 3	For A4 closures
1, 2 ...6	For B4 closures

Shot gun protection enclosure

C	With protection enclosure
N	Without protection enclosure

Type of splicing trays

OPGW cable type (*)					
		(A) CC with plastic loose tube	(B) Metal loose tubes only		
Cable type	Cable dia. (mm)	Max. CC tube dia. (mm)	Max number of metal tubes	Select	
OPGW	9-12	7.5	3	A	
	12-14	10.5	3	B	
	14-16	12.5	3	C	
	16-18	14	3	D	
FO cable	5-19	N/A	N/A	E	

1st cable feed-through

Same options are for 2nd cable feed-through, except option E



www.commscope.com

Visit our website or contact your local CommScope representative for more information.

© 2016 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services.

PS-317200.1-AE (01/16)